



Mobile



Cellular



Cloud



Wireless Locking



Embedded



Enterprise

Smart Native Integration with Top-Rated Wireless Trilogy Networkx Networked PIN/Prox Access Locks



EASY INSTALL
Replaces any door lock, on any door type, neatly, quickly

MORE AFFORDABLE
Lowest labor & equipment costs without sacrificing top electronic access features

EASY NETWORK
No wires to run to doors. Uses customers' existing network or Ethernet & multi-lock gateways & optional repeaters

CENTRALLY MANAGED
Auto-Schedule program updates, queries, or free access by time, by door & more New Real-Time Platform Integration Options

USERS
Supports thousands of PIN, ID or iLock App users. Easily added/removed local or remotely

GLOBAL LOCKDOWN
or unlock in seconds from the server or any lock

Intermix Wireless Access Locks with Control Panels, or use alone, via 802.11 or Ethernet network

P/DL6200 & prox/PIN cylindrical or mortise version P/DL6500 models

Based on Trilogy™, the #1 electronic standalone access locks, Networkx™ Locking Products are networked to save staff labor, eliminating door-to-door programming and audit trail retrieval, by communicating wirelessly via Ethernet or 802.11B/G, all while providing the ultra dependability, functionality & long battery life, original Trilogys are known for. The expanded Networkx line, for every type of door, combines to provide a quick, easy, economical access system for up to 2000 doors and 5000 users, with advanced features & functions, e.g., automatic schedules, event logs. But, with no wires to run, and no access panels or power supplies to buy or install, it can be a great time and budget saver for buildings, campuses or office suites. At its simplest, it's one Grade 1 wireless lock per door, installed in about an hour, all communicating to a single Gateway (your choice of gateways controls up to 63 locks), networked to any non-dedicated Windows-based PC. In addition to Wireless Trilogy Networkx' unsurpassed battery-life, exceeding 5 years, they feature new network-wide capabilities, executed from any lock or the network's PC, including emergency priority global lockdown deployed in seconds, and you can activate (non-priority) system-wide free-passage or locking modes from the PC. For real-time access applications, Networkx Locks offer enterprise network integration with several leading platforms.

- **Trilogy Networkx Locks communicate wirelessly via Ethernet, Bluetooth LE or 802.11B/G** for a comprehensive wireless networked door access control system, eliminating door-to-door programming and audit trail retrieval and providing all standalone Trilogy lock functionality plus new network-wide and emergency lockdown features.
- **Unsurpassed 5-year+ battery life, typical.** (Automatic battery status reports at the PC; visual and audible low-battery status indicators at lock(s).)
- **Trilogy Networkx and gateway modules have an integral transceiver for highly-efficient 900MHz bidirectional communications**, for longer range and less interference than with more common 2.4GHz spread spectrum devices. Alarm Lock devices require NO wiring; NO splitters or repeaters; NO hardwiring to the host/server; NO extra power supplies; and NO access controller/panels.
- **In seconds, emergency global lockdown can be activated from the Networkx PC, any Network lock or Keyfob (RR-4BKEYFOB).** (This priority emergency command is lightning-fast system-wide and supersedes all scheduled programs or updates, etc. However, if desired, locks may be selectively programmed to be excluded from emergency global lockdown function, i.e., they will ignore the command.) New! Flashing Lock-Down indicator on inside door reassures occupants: Secure Campus '23 Award Winner
- **System-wide free-passage enable or disable**, can likewise be activated from the PC/Server

- **Locks easily retrofit standard locks and support up to 5000 users with 3-6 digit numeric PIN codes and PDL-Series also support prox ID card users** (virtually all HID™ format proximity technology ID cards or credentials. HID iClass supported in select 8000 series models.)
- **On demand, in seconds, wirelessly change users, schedules, lock features or retrieve audit trails of up to 40,000 events/lock from any networked PC.** (Note: Transaction processing time is dependent upon system capacity, the more locks/gateways and the more data to be up/downloaded, the longer the time.)
- **Unattended programming updates or event log retrievals can be scheduled to run automatically**, saving manpower and productive time.
- **Seamless upgrade path for original Trilogy users:** Intermix with existing Trilogy standalone lock installations and share one database and familiar Trilogy lock and software functions: Trilogy Wireless Networkx Locks seamlessly integrate in an existing Alarm Lock Trilogy standalone door access system and share the same single CA4k V1.2. Existing Trilogy users can easily add one wireless Networkx Lock, or as many as two thousand, to an existing system seamlessly with no downtime.
- **Secure 128bit AES PC encryption and proprietary RF-link lock communication encryption** protects the system from interference or tampering (WEP or WPA compatible with wireless modem).
- **Remote System Management:** VPN-connection /remote capability for accessing the Networkx System and controlling up to all 2000 locks, with all the security and peace-of-mind of your IT network. (No special modems required.)
- **Wireless locks are fully keypad programmable** and can be up and functioning even before their wireless network is configured, so IT departments don't have to coordinate with physical security departments or locksmiths
- **Minimizing hardware & installation costs, a single gateway module can interface between the PC network and up to 63 Networkx locks**, with a range of up to 900' clear field range or up to 200' depending on building construction. At its maximum, a Trilogy Networkx system can comprise up to 32 gateways for the networking of up to 2000 locks or access controlled doors, using cost-saving/efficient Gateways & Expanders for easiest networking
- **Enterprise Software Integration Options for real-time access provided with Continental, Lenel & AirAccess and All-New Cloud-Based MVP Access Platform**

Continental Enterprise



Advanced Wireless Access Control for Business,

- Wall- or ceiling-mountable, compact gateway modules are available in wireless/hardwired and PoE versions (with Power Over Ethernet (POE) option). The hybrid model connects using either 802.11, Ethernet cable or 100Base-TX (using RJ45 Jack); wired version uses an RJ-45 Ethernet cable. Network communications support both wired Ethernet 10BaseT and wireless 802.11
- Lock programming, user- and usage-data are stored locally at the battery-powered lock for uninterrupted door access usage in a power outage or server offline situation

Enterprise Networks, Real-Time Performance

- Network locks can be used as wireless, single-door controllers in real time too
- Use with AirAccess Cloud-Hosted Platform; MVP Access, Continental Enterprise or, Lenel OnGuard[®]

Trilogy Network Lock Specifications:

- Weatherproof locks for indoor/outdoor use with wide operating temperature range (-31 to 151° degrees F).
- Cylindrical models boast industrial strength BHMA Grade 1 durability and all models feature vandal-resistant all-metal keypad for PIN codes.
- PDL versions, HID Prox. Reader (HID iClass also supported in select 8000 Series models.).
- ADA-compliant leversets.
- Easy-to-install modified ANSI A115 Series door prep; easily and neatly retrofit standard cylindrical knobsets and mechanical standalone locks, in under an hour. Non-handed
- 3 hour UL fire-rated deadlatch.
- Supports 1-5/8 to 1-7/8" door thickness; 2-3/4" backset (2-3/8" available.)
- Manual key override standard; most IC cores also supported on interchangeable core models.
- Wide choice of 3 Architectural finishes (US3 polished brass, 26D satin chrome, 10B duronodic) and IC core preps (6-7pin).

Ordering Information:

PDL6200 Cylindrical Trilogy Network[™] PIN/Prox. Wireless Access Control Lock with built in HID proximity ID card reader door position switch/ request to exit, flashing lock-down indicator on inner door,, full-metal digital keypad, integral bi-directional radio, 4-C cell battery-operated (batts. supplied), serial number ID card, standard format SCI keyway for manual key override, 4-7/8" ASA Strike (incldd).

DL6200 Cylindrical Trilogy[®] Networkx PIN-Code Wireless Access

Up to 2000 locks and a PC communicate wirelessly through bidirectional Gateways- eliminating the need for door-to-door programming and audit trail retrieval. System Management with Enterprise Solutions:

Continental Enterprise

AirAccess



Control Lock, as above, with full-metal digital keypad only.

PDL6600 Mortise version Networkx PIN/Prox. lock, similar to 6200 Series above.

DL6600 Mortise version Networkx PIN-code only lock, similar to 6200 Series above.

AA-KIT1A AIRACCESS Starter Kit (just add choice of door tech for real-time Trilogy Networkx Mgt for full info see ALA537 Spec Sheet, Network Locks or NetPanels, or go to: www.airaccess.com or ask any Alarm Lock Rep.

NETWORKPANEL Also 1-Door Wireless NetPanel for use with wiegand reader, ideal for gate control etc.

Network Interface

INTERFACE: Ethernet 10Base-T or 100Base-TX (using RJ45 Jack)

PROTOCOLS: TCP/IP, UDP/IP, DHCP 802.11 Wireless Specifications

WIRELESS STANDARDS: IEEE 802.11b; 802.11g

FREQUENCY RANGE: 2.412 - 2.484 GHz

OUTPUT POWER: 14 dBm + 1.5 dBm/-1.0 dBm

MAXIMUM RECEIVE LEVEL: -10dBm (with PER < 8%)

DATA RATES WITH AUTOMATIC FALLBACK: 54Mbps - 1Mbps

RANGE: Up to 328 feet indoors

MODULATION TECHNIQUES: OFDM, DSSS, CCK, DQPSK, DBPSK, 64 QAM, 16 QAM



INTERFACE: Wireless 802.11b, 802.11g and 10/100 Ethernet

PROTOCOLS: TCP/IP, UDP/IP, DHCP

SECURITY

- IEEE 802.11 - PSK with AES Encryption 128-bit Encryption
- 128-bit AES Rijndael encryption

AL Radio Link

- 900 MHz GFSK, 50 channels, 10mW power output

VOLTAGE: 5 - 6 volts AC/DC

OPERATING TEMPERATURE: -20° to 60°C (-4° to 140°F)

STORAGE: -40° to 85°C (-40° to 185°F)

AVERAGE POWER CONSUMPTION:

- 1300 mW (WLAN mode; maximum data rate)
- 300 mW (WLAN mode; idle)
- 750 mW (Ethernet Mode)

PEAK SUPPLY CURRENT: 650 mA

INPUT VOLTAGE: 5 - 6 volts AC/DC

OPERATING TEMPERATURE: -31 to 151° degrees F

STORAGE TEMPERATURE: -40° to 85°C (-40° to 185°F)

Easier Networking with Gen. 3 Gateways - Now with Offline-Preconfiguration from any Smart Device (63 Locks/Gateway)



AL-IM3-80211 Gen. 3 Hardware & Wireless Gateway

The Trilogy Networkx 3rd Generation Gateways interface up to 63 Networkx Locks with a PC network. The new 80211 model now features networking via either a hardwire Ethernet connection &/or wirelessly via a bi-directional radio. Similar in function to the original Networkx Gateway Modules, and able to be intermixed with them, but now featuring dual mode installation flexibility and new "Offline-Preconfiguration" from any smart device or PC/laptop, i.e., enabling setup prior to getting on the job-site. Gen 3 Gateways require CA4K V1.2, support up to 7 of the same AL-IME2 Expanders (which extend the range up to 100 feet); 3 LED indicators display Gateway's operational status. AC Xformer supplied; ceiling/wall mount.

(Note: Original Gateways still supported)



AL-IM3-POE Gateway

With all the features & functionality of the above, but AL-IM3-POE (Power Over Ethernet) Hardwired Gateway interfaces Networkx locks with a PC network with hardwire Power-Over-Ethernet. Gen 3 Gateways require CA4K V1.2, support up to 7 of the same AL-IME2 Expanders which extend the range up to 100 feet); 3 LED indicators display Gateway's operational status. Ceiling/Wall Mount.



AL-IME2-EXP Expander


Trilogy[®] Networkx[™] Expander extends the coverage area BOTH Gen 2 & 3 Series Gateways to Trilogy Networkx Locks within a PC network, allowing greater distances for the placement of up to a maximum rated capacity of 63 Networkx locks per Version 2 or 3 Gateways. Ceiling/Wall Mount.



AL-IME2-PIE Plug-in Expander

As above, this Plug-In Expander extends the coverage area of either Gen 2 or 3 Series Gateways.

NEW!



NEW MVP ACCESS[™] CLOUD-HOSTED REMOTE ENTERPRISE ACCESS CONTROL/LOCKING/SECURITY/VIDEO

New ACaaS platform combines CA4K Enterprise management, plus secure cloud-based advantages & new integration options for several to thousands of users, and a few to hundreds of doors. Get up & running in a few quick EZ steps; No on-premises PC or database required. Supports full range of Continental panels & Alarm Lock Networkx locks. Remote lockdown, threat-level management & door control from anywhere w/ MVP Admin App. SMS & Email status & emergency notifications. MFA & iLock Bluetooth Mobile Credential User App. Real-time view & report asstd. events to central station. Embedded Facility Map. New video intercom, VMS & Visitor Mgt integration.

Campus, Healthcare & Office Security Management

NOTE: Part numbers are either prefix **DL** for digital PIN code locks or **PDL** for digital locks with added built-in Prox ID Card Reader

P/DL6200: Cylindrical Lock

- Provide all standalone Trilogy lock functionality plus new network-wide and emergency lockdown features
- 5000 users with 3-6 digit PINs or HID* ID cards
- Includes Door Position Switch/Request to Exit
- Flexible System Monitoring, Control & Programming
- Unsurpassed 5-year+ battery life, typical, using 4 C-cell off-the-shelf batteries (supplied)
- Grade 1 durability, rugged clutch mechanism
- **PDL6200** with built in HID prox reader (shown left) accepts most HID Proximity cards and keyfobs; **DL6200** has keypad only; Prox only model available
- For Prox iClass™ ID cardholder support with DPS/REX, specify model **PDL8200**
- Flashing Lock Down Indicator on Inside Door
- All Trilogy Models now weatherproof as standard -31 to 151°F (-35 to 66°C)



PDL6300 Double-sided Cylindrical Prox Lock

- Double-sided Trilogy lock functionality from 2 sides of the door; PIN/Prox access logged coming & going
- Built-in HID prox reader accepts most HID Proximity cards and keyfobs
- Rugged clutch mechanism and Grade 1 durability ensure long life
- Flexible System Monitoring, Control & Programming
- Long life battery operated; 4AA batteries, 60,000 cycles, typ.
- All Trilogy Models now weatherproof as standard -31 to 151°F (-35 to 66°C) - A jetway favorite



P/DL6600: Mortise Lock

- Keyless Access Lock for mortise door prep
- High security mortise locking
- Flexible System Monitoring, Control & Programming Weatherproof and long-life battery operated
- Includes Door Position Switch/Request to Exit
- 1-3/8" mortise cylinder included
- Choice of classroom or deadbolt functions & finishes
- **PDL6600** with built in HID prox reader (shown left) accepts most HID Proximity cards and keyfobs; **DL6600** has keypad only; Prox only model available
- For Prox iClass™ ID cardholder support with DPS/REX, specify model **PDL8600**
- All Trilogy Models now weatherproof as standard -31 to 151°F (-35 to 66°C)



P/DL1300NW: Narrow Stile Lock Trim

- Add keyless access, automatic lock & free passage schedules to glass doors; plus add remote keyfob support and emergency global lockdown in seconds
- Aluminum door retrofit outside trim for most Adams Rite® Series Latch Locks (1850, 1950, 4710, 4070, 4730, 4900 Series & MS1850S and MS1950S Series)
- 5000 users with 3-6 digit PINs or HID* ID cards; Flexible System Monitoring, Control & Programming
- Long-life battery operated
- **PDL1300NW** with built in HID prox reader (shown right) accepts most HID Proximity cards and keyfobs; **DL1300NW** has keypad only
- All Trilogy Models now weatherproof as standard -31 to 151°F (-35 to 66°C)



P/DL1300NWET: Narrow Stile Exit Trim

- For use with Jackson®, Dor-O-Matic®, Von Duprin®, Dorma®, Arrow®, DCI® & Corbin® panic devices. †NOTE: Must use P/DL1350NWET or P/DL1325NWET with Dor-O-Matic, 2090, Jackson 1095 & Dorma 5300 as they require more than 85° rotation. Dor-O-Matic, Jackson and Dorma devices require thumb-turn or knob; must purchase separate tailpiece assembly

NETDK/NETPK: Networx® Wireless Keypads

- Global lockdown and passage from keypad or PC, schedules, 35K event log, door position status indicator, request-to-exit, door ajar/kick-in, remote release options
- Ideal for use with strikes, mags, electrified exit devices
- 5000 users with 3-6 digit PINs or HID* ID cards
- Versatile for indoors or outside, ideal for education, healthcare, government, airports, courts & retail
- Familiar Trilogy operation; flexible system monitoring, control & programming
- **NETPK** with built in HID prox reader accepts most HID Proximity cards and keyfobs; **NETDK** has keypad only
- All Trilogy Models now weatherproof as standard -31 to 151°F (-35 to 66°C)



(Note: Keypads currently not supported by Enterprise Platforms)

ETDLN/ETPDN: Exit Trim

- Add Trilogy Networx keyless pushbutton convenience and labor-savings to any panic exit bar
- Rugged clutch mechanism insures long life and durability
- Flexible system monitoring, control & programming
- Models available for Von Duprin™, Sargent™, Yale™, Corbin/Russwin™, Dorma™, Marks M9900 or Arrow™ push bars
- Long-life battery operated
- **ETPDN** with built in HID prox reader (shown right) accepts most HID Proximity cards and keyfobs; **ETDLN** has keypad only; Prox only model available
- For Request-to-Exit, specify model **ETPDN-RX**
- For Prox iClass™ ID cardholder support with REX, specify model **ETPDNI-RX**
- All Trilogy Models now weatherproof as standard -31 to 151°F (-35 to 66°C)



ArchiTech™ Customizable Networx Locks are also available with designer, minimalist look & concealed electronics in choice of multi-tech readers and hundreds of styles & finishes in the ArchiTech™ line, www.architechnetworx.com

(Model N90L w/ Multi-Tech Reader, shown)



Top-Rated Trilogy Networkx® Wireless Networked Keyless Entry Access Locks, Integrated with Continental Enterprise & AirAccess Hosted Access Systems*

Model & Feature	P/DL6200	P/DL6600	PDL6300	P/DL1300NW	ETDLN, ETPDN	NETDK, NETPK
Lock Type	Cylindrical	Mortise	Cylindrical	Narrow stile (also PDL1300NWET series for use w/ exit device)	For use with exit device	Keypad
User Codes	5000	5000	5000	5000	5000	5000
Code Length	3-6 digits	3-6 digits	3-6 digits	3-6 digits	3-6 digits	3-6 digits
Programming	Keypad / PC	Keypad / PC	Keypad / PC	Keypad / PC	Keypad / PC	Keypad / PC
Vandal-Proof Keypad	All metal, 12 button	All metal 12-button	All metal 12-button	All metal, 12 button	All metal, 12 button	All metal 12-button
Trim w/Rugged Clutch	Straight or curved lever	Straight or curved lever	Straight or curved lever	Straight or curved lever	Straight or curved lever	
Audit Trail Events	35000	35000	40000	35000	40000	35000
Scheduled Events	500	500	500	500	500	500
Reader/Credential Support	PDL6200 for HID Prox; PDL8200 for iClass support	PDL6600 for HID Prox; PDL8600 for iClass support	HID Prox	PDL1300NW for HID Prox	ETPDN for HID Prox; ETPDNI for iClass support	NETPK for HID Prox
Lockdown w/ Flashing Bar (Privacy)	Global lockdown via lock, server or optional keyfob	Global lockdown via lock, server or optional keyfob	Global lockdown via lock, server or optional keyfob	Global lockdown via lock, server or optional keyfob	Global lockdown via lock, server or optional keyfob	Global lockdown via lock, server or optional keyfob
Door Position Switch †	PDL6200; PDL8200 with iClass support	PDL6600; PDL8600 with iClass support				
Request to Exit †	PDL6200; PDL8200 with iClass support	PDL6600; PDL8600 with iClass support			ETPDN-RX; ETPDNI-RX with iClass support	
Weather-Proof -31 to 151° F	Standard	Standard	Standard	Standard	Standard	Standard
Handing	Non-handed	Handed	Non-handed, fully field reversible	Non-handed, fully field reversible	Non-handed, fully field reversible	
Door Thickness	1-5/8 to 1-7/8" (others on request)	1-5/8 - 1-7/8"	1-5/8 to 1-7/8" (others on request)	1-3/4"	1-5/8 to 1-7/8" (others on request)	
Backset	2-3/4" (included); 2-3/8" option.	2-3/4" (included)	2-3/4" (included)	31/32, 1-1/8 & 1-1/2"; Stile Thickness 1-3/4"		
Cylinder	Large key-in-knob, incld -or- IC Prep for Best/Falcon/Arrow (cylinder not incldd.)	Generic mortise cylinder supplied	Large key-in-knob, incld -or- IC Prep for Best, only	1-1/4" mortise cylinder, supplied; for Best, Falcon, Arrow prep cam and housing available (cylinder not incldd.)	Generic rim cylinder supplied. For other manufacturers' cylinders, adapters can be ordered separately	
Special Order Cylinders	Yale, Medeco, Sargent, Corbin/Russwin, Schlage					
Relay Options	Yes	Yes	No	No	Yes	Yes
Battery/Cycles Typical	4 C cells; 500,000 or up to 5 years	5AA; 60000	4AA; 60,000 or up to 3 - 4 years	4AA; 100,000 or up to 3 - 4 years	4 C cells; 500,000 or up to 5 years	4 C cells; 500,000 or up to 5 years
Ratings	BHMA Grade 1 Lockset; 3hr. Fire Rated UL	3 Hour fire rated UL	3 Hour fire rated UL	3 Hour fire rated UL	3 Hour fire rated UL	
Architectural Finishes	US26D, US10B	US26D, US10B, US19	US26D, US10B	US26D, US10B, US19	US26D, US10B, US19	US26D, US10B

Note: Standard finishes are US26D Satin Chrome & 10B Duronodic. Consult factory for any other finishes. All products proudly backed by 2-year factory warranty.

TRIOLOGY NETWORKX™ ORDERING INFORMATION:

PDL6200 Cylindrical Trilogy Networkx PIN/Prox. wireless access control lock with built in HID proximity ID card reader and Door Position Switch/Request to Exit feature

- Flashing Lock Down Indicator on Inside Door

DL6200 As above, with full-metal digital keypad only

PDL8200 As above, with iClass support

PDL6600 Mortise Trilogy Networkx PIN/Prox. wireless access control lock with built in HID proximity ID card reader and Door Position Switch/Request to Exit feature

DL6600 As above, with full-metal digital keypad only

PDL8600 PIN/Prox Model as above, with iClass support

PDL6300 Cylindrical Trilogy Networkx double-sided PIN/Prox. wireless access control lock with built in HID proximity ID card reader

PDL1300NW Networkx narrow stile wireless access prox lock trim with built in HID proximity ID card reader

DL1300NW As above, with full-metal digital keypad only

PDL1300NWET Networkx narrow stile exit trim with built in HID proximity ID card reader‡

DL1300NWET As above, with full-metal digital keypad only‡

ETPDN Trilogy Networkx wireless access lock trim with built-in HID proximity ID card reader

ETDLN As above, with full-metal digital keypad only

ETPDN-RX Trilogy Networkx wireless access lock trim with built-in HID proximity ID card reader with Request to Exit feature

ETPDNI-RX As above, with iClass support

NETDK DK Wireless Keypad, only

NETPK DK Wireless Keypad with built-in HID proximity ID card reader

AL-IME3-80211 Gen 3 Wired/Wireless Gateway

AL-IME3-POE Gen. 3 Gateway, Power Over Ethernet, No AC power required (Supports Gen 2 Expanders)

AL-IME2-EXP Gen. 2 Wireless Expander (supports Gen 2/3 Gateways)

AL-IME2-PIE Gen. 2 Plug-in Wireless Expander, AC power required

RR-4BKEYFOB Optional 4-button remote keyfob

AL-NSG Optional Gateway Simulator Aid

AL-NSM Optional Site Survey Tool for Networkx Gateways

AA-KIT1A AIRACCESS Starter Kit for real-time Trilogy Networkx Mgt for full info see ALA537 Spec Sheet, or go to: www.airaccess.com or ask any Alarm Lock Rep.

MVP Access App Featuring Mobile credentials w/ geo-fencing, Multifactor Authentication (MFA) & remote administrator functions, global/area-specific unlock or lockdown, etc. (IOS or Android) (For Full Info See MVP Spec Sheet A872)

MVP-IME3-POE Dedicated MVP POE Gateway, Gen. 3 Power Over Ethernet, No AC power required

MVP-IME3-80211 Dedicated MVP Combo Gateway, Gen 3 Wired/Wireless, supports wireless or hardwire Ethernet connection

Napco Access Pro, Alarm Lock, Trilogy, MVP Access, Networkx, ArchiTech, AirAccess and Continental are trademarks of NAPCO Security Technologies, Inc. All others are trademarks of their respective companies.



*System Integration Note: Integrated Lock Options vary by System/Application, please consult Napco Access Pro Sales &/or Tech Docs. Example, for use with AirAccess Hosted Systems, models with door-position monitoring are recommended.

**Note: Feature Sets are subject to change.
A833A.10.2024



355 BAYVIEW AVE. | AMITYVILLE, NY 11701 | 1.800.645.9445 | 631.842.9400 | FAX 631.789.9292 | www.cicaccess.com | www.napcoaccesspro.com